

## Test Report

No.: GZHGR2009023720

Date: Sep 10, 2009


Page 1 of 4

ZHONGSHAN SHI SONGLIN FURNITURE CO., LTD  
B BLOCK, JINLI INDUSTRIAL ZONE, SANXING ROAD, SALANG VILLAGE, SANJIAO TOWN,  
ZHONGSHAN CITY, GUANGDONG PROV., CHINA 528400

The following sample(s) was / were submitted and identified on behalf of the client as:

Sample Description : SL-A2 网椅(OFFICE CHAIR)  
Style / Item No. : SL-A2  
Manufacturer : SONGLIN FURNITURE  
Test Performed : Selected test(s) as requested by applicant  
Sample Receiving Date : Aug 26, 2009  
Sample Resubmission Date : Sep 09, 2009  
Test Performing Date : Aug 26, 2009 to Sep 10, 2009  
Test Result(s) : For further details, please refer to the following page(s)

Signed for and on behalf of  
SGS-CSTC Co., Ltd.

  
Bill Wang  
Senior Engineer

This document is issued by the Company subject to its General Conditions of Service printed overleaf, available on request or accessible at [http://www.sgs.com/terms\\_and\\_conditions.htm](http://www.sgs.com/terms_and_conditions.htm) and for electronic format documents, subject to Terms and Conditions for Electronic Documents at [www.sgs.com/terms\\_e-document.htm](http://www.sgs.com/terms_e-document.htm). Attention is drawn to the limitation of liability, indemnification and jurisdiction issues defined therein. Any holder of this document is advised that information contained hereon reflects the Company's findings at the time of its test only and within the limits of Client's instructions, if any. The Company's sole responsibility is to its Client and this document does not exonerate parties to a transaction from exercising all their rights and obligations under the transaction documents. This document cannot be reproduced except in full, without prior written approval of the Company. Any unauthorized alteration, forgery or falsification of the content or appearance of this document is unlawful and offenders may be prosecuted to the fullest extent of the law. Unless otherwise stated the results shown in this test report refer only to the sample(s) tested and such sample(s) are retained for 30 days only.



## Test Report

No.: GZHGR2009023720

Date: Sep 10, 2009

Page 2 of 4

Test Conducted: ANSI/BIFMA X5.1 -2002 General -Purpose Office Chair – Tests, American National Standard for Office Furniture. Type of chair: Type I & II & III

Test Items	Test Methods & Requirements	Test Results
Back Strength Test - Static - Type I – Functional Load (Clause 5.4)	No loss of serviceability when 890N (200lbs.) is applied for 1 min. Applied 90° to the back at 16in. above the seat.	Pass
Back Strength Test - Static - Type I – Proof Load (Clause 5.4)	No sudden and major change in the structural integrity (loss of serviceability is acceptable) when 1334N (300lbs.) is applied for 1 min. Applied 90° to the back at 16in. above the seat.	Pass
Back Strength Test - Static - Type II & III – Functional Load (Clause 6.4)	No loss of serviceability when 667N (150lbs.) is applied for 1 min. Applied 90° to the back at 16in. above the seat.	Pass
Back Strength Test - Static - Type II & III – Proof Load (Clause 6.4)	No sudden and major change in the structural integrity (loss of serviceability is acceptable) when 1112N (250lbs.) is applied for 1 min. Applied 90° to the back at 16in. above the seat.	Pass
Base Test – Static (Clause 7)	No sudden and major change in the structural integrity under 11,120N (2500lbs.) compressions for 1 min. The weight is then removed and reapplied for 1 min.	Pass
Drop Test – Dynamic – Functional Load (Clause 8.4)	No loss of serviceability when 102kg (225lbs.) weight free falls from 6in. height to the center of the seat.	Pass
Drop Test Dynamic – Proof Load (Clause 8.4)	No sudden and major change in the structural integrity (loss of serviceability is acceptable) when 136kg (300lbs.) weight free falls from 6in. height to the center of the seat.	Pass
Swivel Test – Cyclic (Clause 9)	No loss of serviceability after 60,000cycles of rotation (360°) under a 102kg (225lbs.) load on the seat at its max. height. Seat shall then withstand another 60,000 cycles of rotation at its lowest seating position. Total 120,000cycles.	Pass
Tilt Mechanism Test – Cyclic – Type I & II (Clause 10)	No loss of serviceability after 300,000cycles under a 102kg (225lbs.) load to the center of the seat	Pass
Impact Test – Cyclic (Clause 11.3)	No loss of serviceability in 100,000cycles impact. A weight of 57kg (125lbs.) free falls onto the seat from 1 in. height.	Pass
Front Corner Load Ease Test – Cyclic – off Center (Clause 11.4)	No loss of serviceability after load each seat front corner with 734N (165 lbs.) for 20,000 cycles, total 40,000 cycles. Note: this test is done after "Impact test" on the same sample.	Pass
Stability Test – Rear Stability (Clause 12.3)	A 79kg (173lbs.) weight is placed to the seat center (strapped as Fig. 12a). Obstruct the chair casters/legs with 13mm (½in.) obstacle. A tipping force is applied to the chair back until the total weight is transferred to the rear support members. The tipping force shall not be less than: Type I and II –89N (20 lbs.), Type III –156N (35 lbs.)	Pass

To be continued...

This document is issued by the Company subject to its General Conditions of Service printed overleaf, available on request or accessible at [http://www.sgs.com/terms\\_and\\_conditions.htm](http://www.sgs.com/terms_and_conditions.htm) and, for electronic format documents, subject to Terms and Conditions for Electronic Documents at [www.sgs.com/terms\\_e-document.htm](http://www.sgs.com/terms_e-document.htm). Attention is drawn to the limitation of liability, indemnification and jurisdiction issues defined therein. Any holder of this document is advised that information contained hereon reflects the Company's findings at the time of its intervention only and within the limits of Client's instructions, if any. The Company's sole responsibility is to its Client and this document does not exonerate parties to a transaction from exercising all their rights and obligations under the transaction documents. This document cannot be reproduced except in full, without prior written approval of the Company. Any unauthorized alteration, forgery or falsification of the content or appearance of this document is unlawful and offenders may be prosecuted to the fullest extent of the law. Unless otherwise stated the results shown in this test report refer only to the sample(s) tested and such sample(s) are retained for 30 days only.

GZHGR 312988



## Test Report

No.: GZHGR2009023720

Date: Sep 10, 2009

Page 3 of 4

Test Items	Test Methods & Requirements	Test Results
Stability Test – Front Stability (Clause 12.4)	The chair is obstructed with a 13mm (½ in.) obstruction to the chair casters/legs. A downward load of 600N (135lbs.) is centered 60mm (2.4in.) from the seat front center edge. The seat shall withstand a 20N (4.5lb.) horizontally from the front seat edge without tipping.	Pass
Arm Strength Test Vertical – Static – Functional Load (Clause 13.4)	No loss of serviceability when 890N (200lbs.) is applied for 1 min. The vertical load is uniformly applied along a 127mm (5in.) length at the apparent weakest point.	Pass
Arm Strength Test Vertical-Static – Proof Load (Clause 13.4)	No sudden and major change in the structural integrity (loss of serviceability is acceptable) when 1334N (300lbs.) is applied for 1 min. The vertical load is uniformly applied along a 127mm (5 in.) length at the apparent weakest point.	Pass
Arm Strength Test Horizontal –Static – Functional Load (Clause 14.4)	No loss of serviceability when 445N (100lbs.) for 1 min. is applied horizontally outward to the armrest at the most forward point of the armrest.	Pass
Arm Strength Test Horizontal – Static – Proof Load (Clause 14.4)	No sudden and major change in the structural integrity (loss of serviceability is acceptable) when 667N (150lbs.) for 1 min. is applied horizontally outward to the armrest at the most forward point of the armrest.	Pass
Back Durability Test – Cyclic – Type I (Clause 15)	No loss of serviceability in 120,000 cycles with a 102kg (225lbs.) in the center of the seat and a 445N (100lb.) 90° to the center of the chair back. For chairs with a back width greater than 406mm (16in.), test at the center of chair back for 80,000cycles and then 102mm (4in.) off-center 40,000 cycles, half to each side.	Pass
Back Durability Test – Cyclic – Type II & III (Clause 16)	No loss of serviceability in 120,000 cycles with a 102kg (225lbs.) in the center of the seat and a 334N (75lb.) 90° to the center of the chair back. For chairs with a back width greater than 406mm (16in.), test at the center of chair back for 80,000cycles and then 102mm (4in.) off-center 40,000 cycles, half to each side.	Pass
Caster / Chair Base Durability Test for Pedestal Base Chair (Clause 17.1)	No loss of service after 2,000cycles over a hard surface with 3 obstacles and 98, 000cycles over a smooth hard surface without obstacles under a 102kg (225lbs.) load on the seat. Test stroke is 762mm (30in.) minimum. The caster should not separate under 22N (5lbs.) pulling force in line with the caster stem after the cycling test.	Pass
Caster / Chair Base Durability Test for Chairs with Legs (Clause 17.2)	No loss of service after 2,000cycles over a hard surface with 2 obstacles and 98, 000cycles over a smooth hard surface without obstacles under a 102kg (225lbs.) load on the seat. Test stroke is 762mm (30in.) minimum. The caster should not separate under 22N (5lbs.) pulling force in line with the caster stem after the cycling test.	NA

To be continued...

This document is issued by the Company subject to its General Conditions of Service printed overleaf, available on request or accessible at [http://www.sgs.com/terms\\_and\\_conditions.htm](http://www.sgs.com/terms_and_conditions.htm) and for electronic format documents, subject to Terms and Conditions for Electronic Documents at [www.sgs.com/terms\\_e-document.htm](http://www.sgs.com/terms_e-document.htm). Attention is drawn to the limitation of liability, indemnification and jurisdiction issues defined therein. Any holder of this document is advised that information contained hereon reflects the Company's findings at the time of its intervention only and within the limits of Client's instructions, if any. The Company's sole responsibility is to its Client and this document does not exonerate parties to a transaction from exercising all their rights and obligations under the transaction documents. This document cannot be reproduced except in full, without prior written approval of the Company. Any unauthorized alteration, forgery or falsification of the content or appearance of this document is unlawful and offenders may be prosecuted to the fullest extent of the law. Unless otherwise stated the results shown in this test report refer only to the sample(s) tested and such sample(s) are retained for 30 days only.

GZHGR 312989



Test Items	Test Methods & Requirements	Test Results
Leg Strength Test -Front Load – Functional Load (Clause 18.3)	No loss of serviceability when a force of 334N (75lbf.) is applied to each front leg individually for 1 minute.	NA
Leg Strength Test-Front Load – Proof Load (Clause 18.3)	No sudden and major change in the structural integrity (loss of serviceability is acceptable) when a force of 556N (125lbf.) is applied to each front leg individually for 1 minute.	NA
Leg Strength Test -Side Load – Functional Load (Clause 18.4)	No loss of serviceability when a force of 334N (75lbf.) is applied once to each front and rear leg individually for 1 minute.	NA
Leg Strength Test -Side Load – Proof Load (Clause 18.4)	No sudden and major change in the structural integrity (loss of serviceability is acceptable) when a force of 512N (115lbf.) is applied once to the front and rear leg individually for 1 minute.	NA
Footrest Durability Test (Clause 19)	No loss of serviceability after 50,000cycles of a 890N (200lbf) load vertical along 102mm (4in.) length of the footrest at the apparent weakest point of the structure.	NA
Arm Durability Test – Cyclic (Clause 20)	No structural breakage or loss of serviceability when a force of 400N (90lbf.) is applied to each arm at a 10° angle ±1° for 60,000cycles	Pass
Out Stop Tests for Chairs with Manually Adjustable Seat Depth (Clause 21)	Place a 70 kg (154 lb) rigid mass in the center of the seat. Hold the seat at its most position. A cable is attached to the most rigid point of the vertical centerline of the seat. Hang a weight of 25 kg (55 lb) on the opposite end of the cable. Release the weight so it can drag the seat move forward rapidly and impact	NA
Tablet Arm Static Load Test (Clause 22)	Apply a load of 68 kg (150 lb) at the apparent weakest position for 5 minutes and remove the load. No sudden and major change in the chair when the application of the load.	NA
Tablet Arm Load Ease Test – Cyclic (Clause 23)	No loss of serviceability to the unit after loading the tablet surface with a weight of 35 kg (77 lb) for a total 100,000 cycles.	NA

Remark: 1) NA – Not applicable;

2) Type of chair:

Type I – tilt chair: a chair with a seat tilts with a counterbalancing force;

Type II – fixed seat angle, tilting backrest: a chair that provides a fixed angle with a tilting backrest;

Type III – fixed seat angle, fixed backrest: a chair that provides a fixed seat angle with a fixed backrest;

3) Photo appendix is included.

\*\*\*End of Report\*\*\*

This document is issued by the Company subject to its General Conditions of Service printed overleaf, available on request or accessible at [http://www.sgs.com/terms\\_and\\_conditions.htm](http://www.sgs.com/terms_and_conditions.htm) and, for electronic format documents, subject to Terms and Conditions for Electronic Documents at [www.sgs.com/terms\\_e-document.htm](http://www.sgs.com/terms_e-document.htm). Attention is drawn to the limitation of liability, indemnification and jurisdiction issues defined therein. Any holder of this document is advised that information contained hereon reflects the Company's findings at the time of its intervention only and within the limits of Client's instructions, if any. The Company's sole responsibility is to its Client and this document does not exonerate parties to a transaction from exercising all their rights and obligations under the transaction documents. This document cannot be reproduced except in full, without prior written approval of the Company. Any unauthorized alteration, forgery or falsification of the content or appearance of this document is unlawful and offenders may be prosecuted to the fullest extent of the law. Unless otherwise stated, the results shown in this test report refer only to the sample(s) tested and such sample(s) are retained for 30 days only.





### PHOTO APPENDIX



SGS authenticate the photo on original report only

This document is issued by the Company subject to its General Conditions of Service printed overleaf, available on request or accessible at [http://www.sgs.com/terms\\_and\\_conditions.htm](http://www.sgs.com/terms_and_conditions.htm) and for electronic format documents, subject to Terms and Conditions for Electronic Documents at [www.sgs.com/terms\\_e-document.htm](http://www.sgs.com/terms_e-document.htm). Attention is drawn to the limitation of liability, indemnification and jurisdiction issues defined therein. Any holder of this document is advised that information contained hereon reflects the Company's findings at the time of its intervention only and within the limits of Client's Instructions, if any. The Company's sole responsibility is to its Client and this document does not exonerate parties to a transaction from exercising all their rights and obligations under the transaction documents. This document cannot be reproduced except in full, without prior written approval of the Company. Any unauthorized alteration, forgery or falsification of the content or appearance of this document is unlawful and offenders may be prosecuted to the fullest extent of the law. Unless otherwise stated, the results shown in this test report refer only to the sample(s) tested and such sample(s) are retained for 30 days only.