

TEST REPORT

Report No. : HL30204/2007

Page : 1 of 2

Date : APR. 02, 2007

FUH SHYAN CO., LTD.

No.27, Cherng Gong One St., Boh Doou Tsuen,
Min Shyong Hsiang, Chia Yi, Taiwan, R.O.C.

The following merchandise was submitted and identified by the applicant as:

Product Description: Castors
Style/Item No.: CT600A/38/F1122
Manufacturer/Vendor: FUH SHYAN CO., LTD.
Country of Origin: Taiwan

We have tested the submitted sample(s) as requested and the following results were obtained:

Test Requested: For compliance with ANSI/BIFMA X5.1-2002 General-Purpose Office Chairs-Tests
Sect. 17. Caster/Chair Base Durability Test - Cyclic


Test Method: According to test procedures of ANSI/BIFMA X5.1-2002

Test Results: ---See attached sheets---

Conclusion: In our opinion, the submitted sample(s) complies with Sect. 17 of ANSI/BIFMA
X5.1-2002 for General - Purpose Office Chair.

Testing Period: 2007/03/14 ~ 2007/04/02

Signed for and on behalf of
SGS Taiwan Ltd.


Owen Cheng
Asst. Manager

This Test Report is issued by the Company subject to its General Conditions of Service printed hereof or available on request and accessible at www.sgs.com. Attention is drawn to the limitations of liability, indemnification and jurisdictional issues defined therein. Unless otherwise stated the results shown in this test report refer only to the sample(s) tested. This test report cannot be reproduced, except in full, without prior written permission of the Company. Any unauthorized alteration, forgery or falsification of the content or appearance of this report is unlawful and offenders may be prosecuted to the fullest extent of the law. 此報告係根據本公司訂定之通用服務條款所製作發給。請注意此報告的印字內容，亦可於www.sgs.com中查閱。對本公司之名稱、位置、資料權等明確標明之，就非另有說明，此報告結果僅對標驗之樣品負責。本報告未經本公司同意請勿複製、對本報告內容作任何之任何未經授權之變更、偽造、竄改或變異。請於此報告發給後立即註銷。

TW4375301

TEST REPORT

Report No. : HL30204/2007

Page : 2 of 2

Test Result: ASNI /BIFMA X5.1-2002 General-Purpose Office Chairs-Tests

Sect 17 Caster/Chair Base Durability Test – Cyclic

Pass

Base on subsection 17.1.4 a) test procedures (Durability Cycling)

--- Attach the chair base with the casters to a cycling device and apply 225 lbs. load to the chair base and operate the machine on

(1) smooth, hard surface without obstacles for 98,000 cycles

(2) smooth, hard surface with obstacles for 2,000 cycles

at 10±2 cycles per minute. (one cycle consist of a

forward and backward stroke – the length of stroke is 30 inches)

Requirements: No structural failure or loss of serviceability.

Base on subclause 17.1.4 b) test procedures (Caster Retention)


Pass

--- At conclusion of durability cycling, apply a load of 5 lbf. to each caster in line with the caster stem centerline.

Requirements: No part of the caster shall separate from the base as a result of the application of 5 lbf. force

- Picture Page -

Sample Appearance



--- End of Report ---

This Test Report is issued by the Company subject to its General Conditions of Service printed overleaf or available on request and accessible at www.sgs.com. Attention is drawn to the limitations of liability, indemnification and jurisdictional issues defined therein. Unless otherwise stated the results shown in this test report refer only to the sample(s) tested. This test report cannot be reproduced, except in full, without prior written permission of the Company. Any unauthorized alteration, forgery or fabrication of the content or appearance of this report is unlawful and offenders may be prosecuted to the fullest extent of the law. 此報告係由本公司訂定之通用服務條款所製作發放，請注意此條款所訂明之限制、責任及管轄權等事項。未經本公司之書面許可，不得部份複製、對本報告內容或外觀之任何未經授權之變更、偽造、竄改或重印。違者將依法究辦。

TW4375302